

- **\$\$MG^XMBGRP(XMGROUP,XMTYPE,XMORG,XMSELF,.XMY,.XMDESC,XMQUIET)**

Creates a new mail group or adds members to an existing mail group. Only local members can be added with this call. There is no API that adds any other type of member. Returns mail group IEN if no error; 0 otherwise.



There is no other equivalent API.

Input Parameters:

XMGROUP	=Mail group name (without the G.), if new mail group. =Mail group IEN or full name (without the G.), if existing mail group.
XMTYPE	Type of mail group. Used only for creating a mail group, otherwise it's ignored. =0—Public (default) =1—Private
XMORG	DUZ of group organizer. Used only for creating a mail group, otherwise it's ignored.
XMSELF	Allow self-enrollment? (0=no; 1=yes) Used only for creating a mail group, otherwise it's ignored.
.XMY	Array of local users to add to the mail group. Only DUZs are accepted (names are not).
.XMDESC	Array of text to put in the description field of the mail group. Used only for creating a mail group, otherwise it's ignored.
XMQUIET	Silent flag. =0—Interactive. Any errors will be displayed. =1—Silent (default). Any errors will be sent in a message to the Postmaster and the user (DUZ) making this call.

Parameters Killed Upon Exit:

XMY